



Suite 555 – 999 Canada Place
Vancouver, BC, V6C 3E1
Tel: 604-484-3597
Fax: 604-687-1715
Email: info@arizonamining.com
Web: www.arizonamining.com

NEWS RELEASE

ARIZONA MINING REPORTS FURTHER DRILLING RESULTS AT HERMOSA-TAYLOR; INCLUDES 87 FOOT INTERVAL ASSAYING 31.7% ZINC, 15.4% LEAD AND 5.0 OPT SILVER WITHIN BROADER 402 FOOT MINERALIZED ZONE

Vancouver, B.C., February 14, 2017 – Arizona Mining Inc. (TSX: AZ) (“Arizona Mining” or the “Company”) announces the results of three (3) exploration drill holes from its current program on the Taylor zinc-lead-silver sulfide deposit located on its 100%-owned Hermosa Project in Santa Cruz County, Arizona. This brings the total number of drill holes reported in the 2016-2017 program to sixty-two (62).

HDS-413 is an angled drill hole (-82 degrees) drilled to infill an area southwest of the previously reported resource area. HDS-413 intersected seven (7) distinct mineralized sulfide horizons which when added together give a total cumulative mineralized thickness of 716 feet (refer to Table I). Six (6) of the mineralized zones are in the Taylor Sulfide zone and one (1) intersected the Taylor Deeps Sulfide zone. Some of the best results in the hole included:

- **402 feet assaying 12.8% zinc, 7.2% lead and 2.3 ounces per ton (“opt”) silver**
 - Including a 87 foot zone which assayed 31.7% zinc, 15.4% lead and 5.0 opt silver
 - Including a 15 foot zone which assayed 17.7% zinc, 18.2% lead and 12.6 opt silver
- **203 feet assaying 4.4% zinc, 3.6% lead and 1.1 opt silver**
 - Including a 21 foot zone which assayed 10.7% zinc, 8.9% lead and 2.6 opt silver
 - Including a 15 foot zone which assayed 14.5% zinc, 10.3% lead and 3.1 opt silver

HDS-406 is an angled drill hole (-85 degrees) drilled to infill an area of the previously reported mineral resource. The drill hole encountered three (3) mineralized veins in the volcanics and four (4) mineralized horizons within the Taylor Sulfide zone and two (2) mineralized horizons in the Taylor Deeps Sulfide zone. When added together the Taylor Sulfide zone intervals have a cumulative thickness of 136.5 feet (refer to Table I). Most notable among the mineralized horizons includes:

- **12 feet assaying 7.5% zinc, 3.7% lead and 1.6 opt silver**
- **71 feet assaying 12.0% zinc, 9.4% lead and 3.0 opt silver**

HDS-407 is a vertical infill drill hole that intersected two (2) mineralized veins; eight (8) mineralized horizons in the Taylor Sulfide zone plus a significant zone of mineralization in the Taylor Deeps Sulfide zone. Most notable among the mineralized horizons is the mineralization in the Taylor Deeps Sulfide zone which assayed:

- **55 feet assaying 10.1% zinc, 9.5% lead and 6.0 opt silver**

For a full list of the vein, Taylor Sulfide and Taylor Deeps Sulfide mineralized intervals from these holes please refer to Table I below.

CEO Jim Gowans commented: “These drill results continue to confirm the continuity of the Taylor Sulfide portion of the deposit and expand the footprint of the new Taylor Deeps zone.”

Table I. ASSAY SUMMARIES FOR HDS-406, HDS-407 & HDS-413

DH_ID	From (feet)	To (feet)	Interval (in feet)	From (meters)	To (meters)	Interval (meters)	Ag opt	Pb%	Zn%	Cu%	Zone*
HDS-406	1379.5	1382	2.5	420.5	421.2	0.8	7.50	0.39	0.70	0.45	Vein
HDS-406	1488	1500	12	453.5	457.2	3.7	1.64	3.68	7.53	0.06	TS
HDS-406	1723	1728	5	525.1	526.7	1.5	2.87	2.80	5.03	0.28	Vein
HDS-406	1901	1905	4	579.4	580.6	1.2	6.07	0.49	1.40	0.17	Vein
HDS-406	1970	2011	41	600.4	612.9	12.5	0.81	1.45	3.52	0.06	TS
HDS-406	2398	2410.5	12.5	730.9	734.7	3.8	1.46	4.39	3.11	0.03	TS
HDS-406	2508	2579	71	764.4	786.0	21.6	2.98	9.42	12.02	0.11	TS
HDS-406	3371	3408	37	1027.4	1038.7	11.3	1.03	2.92	3.11	0.25	TDS
HDS-406	3532	3535.5	3.5	1076.5	1077.6	1.1	20.24	2.72	1.47	1.13	TDS
HDS-407	572	587	15	174.3	178.9	4.6	1.65	1.50	4.94	0.02	TS
HDS-407	912	972	60	278.0	296.3	18.3	1.03	1.22	2.24	0.01	Vein
Including	947	957	10	288.6	291.7	3.0	2.67	4.09	10.47	0.04	Vein
HDS-407	1047	1062	15	319.1	323.7	4.6	1.00	1.19	1.75	0.03	Vein
HDS-407	2037	2092	55	620.8	637.6	16.8	0.51	1.31	1.83	0.04	TS
HDS-407	2242	2286.5	44.5	683.3	696.9	13.6	0.69	1.14	1.49	0.20	TS
HDS-407	2652	2687	35	808.3	819.0	10.7	0.85	2.48	2.73	0.03	TS
HDS-407	2814.5	2822	7.5	857.8	860.1	2.3	0.98	3.14	3.05	0.01	TS
HDS-407	2987	3012	25	910.4	918.0	7.6	0.41	1.23	1.00	0.01	TS
HDS-407	3139.5	3152	12.5	956.9	960.7	3.8	3.74	2.76	1.84	0.13	TS
HDS-407	3181.5	3197.5	16	969.7	974.6	4.9	2.22	3.71	1.27	0.13	TS
HDS-407	3277	3332	55	998.8	1015.5	16.8	5.98	9.52	10.14	0.27	TDS
HDS-413	1197	1222	25	364.8	372.4	7.6	1.13	0.97	1.89	0.03	TS
HDS-413	1765	2167	402	537.9	660.5	122.5	2.29	7.15	12.75	0.17	TS
Including	2007	2094	87	611.7	638.2	26.5	5.00	15.44	31.65	0.28	TS
HDS-413	2277	2325	48	694.0	708.6	14.6	7.40	7.47	8.23	0.40	TS
Including	2295	2310	15	699.5	704.1	4.6	12.57	18.21	17.70	0.64	TS
HDS-413	2482	2685	203	756.5	818.3	61.9	1.09	3.61	4.36	0.05	TS
Including	2487	2496	9	758.0	760.7	2.7	6.75	22.50	30.33	0.57	TS
Including	2597	2618	21	791.5	797.9	6.4	2.62	8.87	10.71	0.09	TS
Including	2647	2662	15	806.8	811.3	4.6	3.05	10.34	14.46	0.06	TS
HDS-413	2753	2772	19	839.1	844.9	5.8	0.87	2.70	1.67	0.01	TS
HDS-413	3202	3211	9	975.9	978.7	2.7	17.62	11.45	8.27	0.25	TS
HDS-413	3352	3362	10	1021.6	1024.7	3.0	3.72	2.36	3.07	0.23	TDS

*TS (Taylor Sulfides)

*TDS (Taylor Deeps Sulfides)

Drill intersections with a combined zinc and lead grade of greater than 9% are highlighted. Taylor Sulfide and Taylor Deeps Sulfide drill intervals are down-the-hole drill widths but are considered to be within +/- 5% of true width based on the dip of the mineralized stratigraphy at 22 degrees. The exception to this are the intervals noted as veins. It is not possible to determine the true width of the veins based on the drill density and no representation is made here regarding true width of the veins.

Qualified Person

The results of the Arizona Mining Inc. drilling have been reviewed, verified and compiled by Donald R. Taylor, MSc., PG, Chief Operating Officer for Arizona Mining Inc., a qualified person as defined by National Instrument 43-101 (NI 43-101). Mr. Taylor has more than 25 years of mineral exploration and mining experience, and is a Registered Professional Geologist through the SME (registered member #4029597).

Assays and Quality Assurance/Quality Control

To ensure reliable sample results, the Company has a rigorous QA/QC program in place that monitors the chain-of-custody of samples and includes the insertion of blanks, duplicates, and certified reference standards at statistically derived intervals within each batch of samples. Core is photographed and split in half with one-half retained in a secured facility for verification purposes.

Sample preparation (crushing and pulverizing) has been performed at ALS Minerals Laboratories, an ISO/IEC accredited lab located in Tucson, Arizona. ALS Minerals Laboratories prepares a pulp of all samples and sends the pulps to their analytical laboratory in Vancouver, B.C. Canada for analysis. ALS analyzes the pulp sample by ICP following a 4-acid digestion (ME-ICP61 for 33 elements) including Cu (copper), Pb (lead), and Zn (zinc). All samples in which Cu (copper), Pb (lead), or Zn (zinc) are greater than 10,000 ppm are rerun using four acid digestion with an ICP – AES finish (Cu-OG62; Pb-OG62; and Zn-OG62) with the elements reported in percentage (%). Silver values are determined by ICP (ME-ICP61) with all samples with silver values greater than 100 ppm repeated using four acid digestion with an ICP-AES finish (Ag-OG62) calibrated for higher levels of silver contained. Any values over 1,500 ppm Ag trigger a fire assay with gravimetric finish analysis. Gold values are determined by a 30 gm fire assay with an ICP-AES finish (Au-ICP21).

About Arizona Mining

Arizona Mining Inc. is a Canadian mineral exploration and development company focused on the exploration and development of its 100%-owned Hermosa Project located in Santa Cruz County, Arizona. The Taylor Deposit, a zinc-lead-silver carbonate replacement deposit, has a resource of 31.1 million tons in the Indicated Mineral Resource category grading 10.9% zinc equivalent (“ZnEq”) and 82.7 million tons in the Inferred Mineral Resource category grading 11.1% ZnEq both utilizing a 4% ZnEq cutoff grade calculated in accordance with NI 43-101 guidelines (refer to the Company’s news release dated October 31, 2016). The Taylor Deposit remains open to the north, west and south over land controlled by the Company and will be aggressively drilled to test the limits of the resource. The Company’s other project on the Hermosa property is the Central Deposit, a silver-manganese manto oxide project.

For additional information please contact:

Susan Muir

Vice-President, Investor Relations & Corporate Communications

Telephone: 416-505-7606

Email: smuir@arizonamining.com

Cautionary Note Regarding Forward-Looking Information

Certain information contained in this press release constitutes forward-looking statements. All statements, other than statements of historical facts, are forward looking statements including statements with respect to the Company's intentions for its Hermosa Project in Arizona, including, without limitation, performing additional drilling and metallurgical testwork on the Taylor Deposit. Forward-looking statements are often, but not always, identified by the use of words such as may, will, seek, anticipate, believe, plan, estimate, budget, schedule, forecast, project, expect, intend, or similar expressions.

The forward-looking statements are based on a number of assumptions which, while considered reasonable by Arizona Mining, are subject to risks and uncertainties. In addition to the assumptions herein, these assumptions include the assumptions described in Arizona Mining's management's discussion and analysis for the year ended December 31, 2015 ("MD&A"). Arizona Mining cautions readers that forward-looking statements involve and are subject to known and unknown risks, uncertainties and other factors which may cause actual results, performance or achievements to differ materially from those expressed in or implied by such forward-looking statements and forward-looking statements are not guarantees of future results, performance or achievement. These risks, uncertainties and factors include general business, economic, competitive, political, regulatory and social uncertainties; actual results of exploration activities and economic evaluations; fluctuations in currency exchange rates; changes in project parameters; changes in costs, including labour, infrastructure, operating and production costs; future prices of zinc, lead, silver and other minerals; variations of mineral grade or recovery rates; operating or technical difficulties in connection with exploration, development or mining activities, including the failure of plant, equipment or processes to operate as anticipated; delays in completion of exploration, development or construction activities; changes in government legislation and regulation; the ability to maintain and renew existing licenses and permits or obtain required licenses and permits in a timely manner; the ability to obtain financing on acceptable terms in a timely manner; contests over title to properties; employee relations and shortages of skilled personnel and contractors; the speculative nature of, and the risks involved in, the exploration, development and mining business; and the factors discussed in the section entitled "Risks and Uncertainties" in the MD&A.

Although Arizona Mining has attempted to identify important risks, uncertainties and other factors that could cause actual performance, achievements, actions, events, results or conditions to differ materially from those expressed in or implied by the forward-looking information, there may be other risks, uncertainties and other factors that cause performance, achievements, actions, events, results or conditions to differ from those anticipated, estimated or intended. Unless otherwise indicated, forward-looking statements contained herein are as of the date hereof and Arizona Mining disclaims any obligation to update any forward-looking statements, whether as a result of new information, future events or results or otherwise, except as required by applicable law.

DRILLHOLE LOCATION MAP

